

Ex d Cable Gland M20 Armored

Cable gland for armored cables hazardous areas

For hazardous area compliance of maintaining a secure connection where the armored cable connects to the camera or junction box. Ex d cable gland is certified for flameproof enclosures. The cable gland suits cable entries with M20x1.5 threads.

> **Certified for ATEX, IECEx**

> **Extended temperature range**



Ex d Cable Gland M20 Armored

General

| | |
|---------------------------|--|
| Supported products | Armored cables ExCam, 10, 25, 95 m (33, 82, 312 ft) |
| Cable routing | For cable diameter: 13.5–21.0 mm (0.53–0.83 in) Thread length: 15 mm (0.6 in) |
| Casing | Nickel-plated brass Color: Metal/Silver |
| Approvals | Environment: IEC/EN 60529 IP66, IP68 Explosion: EN/IEC 60079-0, EN/IEC 60079-1, EN/IEC 60079-7, EN/IEC 60079-31 |
| Certifications | Model key: Cable gland type ADE 4F No 7 |

ATEX: II 2 G Ex db/eb IIC, II 2 D Ex tb IIIC
Certificate: INERIS 12 ATEX 0032 X
IECEX: Ex db/eb IIC, Ex tb IIIC
Certificate: IECEX INE 12.0025X
-60°C < Tamb < +140°C

Included accessories

Documentation

Environmental responsibility:

axis.com/environmental-responsibility